

GRIPPER SLING SINGLE MOUNT



Arizona Archery Enterprises
2781 N. Valley View Drive • Prescott Valley, AZ 86314
Phone: 928-772-9887 • Fax: 928-772-6287
www.arizonaarchery.com



AAE's Gripper HR Sling combines our Hot Rodz wrist sling with our Gripper Single and Double w/Quick Disconnect.

The tapered engagement on the Gripper, offers maximum surface area contact for the ultimate in security, while using 7075 aluminum to provide the most rigid connection to the bow possible. AAE's new proprietary BLS (Bolt Lock System) automatically micro drives the parts out when the user loosens the bolt. The BLS prevents the unwanted seizing or binding common with anodization allowing the user to quickly and easily make last minute adjustments. Laser etched reference marks have been added to both axis to monitor the finest of movements.

To mount the Gripper HR Sling, use the included mounting bolt. Slide the bolt into the slot of the "Mount" of the bracket. Mount the bracket as level as possible as un-level mounting will result in a curved motion when adjusting each axis. Once securely mounted, adjust the up/down and in/out to the desired position.

To make adjustments to the length of the sling rope, loosen the set screws on the mount. Once you have it the length you want, tighten the set screws.

MOUNT

5/16-24 x 5/8
SHCS ALLY

SLING ROPE

BAR END

5/16-24 x 5/8
SHCS ALLY

