

The **PRO BLADE**™ Target Arrow Rest has been designed with the help of some of the top tournament compound shooters in the world. This rest has been built to meet their exacting standards for accuracy, durability, and ease of adjustment. Each **PRO BLADE**™ has been CNC machined to very high tolerances. We believe this is the finest blade-style rest ever produced.

Mount the **PRO BLADE™** to the side of your bow with the enclosed 5/16-24x3/4" mounting bolt. Make sure the rest is at right angles (90-degrees) to your bowstring or riser. Now move your center shot to align your arrow with the center of your bow. This can be done by loosening the horizontal micro-adjustment thumb screw to move the block left or right. There are three screw holes that the horizontal socket-head screw can be placed into to allow for more adjustment if necessary.

There are two ways to move the launcher blade. You can use the vertical micro-adjustment thumb screw. Simply loosen the vertical socket-head screw (located on the side of the mount) and turn the vertical micro-adjustment thumb screw. To rotate the launcher arm, loosen the locking set screw (located under the horizontal adjustment block) and the locking socket-head screw (located on the side of the horizontal adjustment block).



Make sure to tighten the locking set screw and locking socket-head screw after adjustment.

The **PRO BLADE™** has an unique raised hex on the launcher arm that matches up with the launcher blades. This allows you to change blades at any time without losing your center shot adjustment. Simply remove the launcher arm socket-head screw and stepped washer and replace the launcher blade making sure that the hex hole is seated correctly before tightening the launcher arm socket-head screw.

PRO BLADE™ launchers are available in three configurations; Standard, Wide, and Freak Blade widths. The Standard blade is for carbon arrows and smaller aluminum shafts. The Wide blade is for the larger aluminum and carbon shafts. The Freak Blade is a narrow blade designed for micro-diameter arrows. All three blades are available in .008″, .010″, and .012″ thickness and two different lengths; Short 1.625″ and Original 1.85″ for a wide range of tuning possibilities.

Mount

